

MATERIAL SAFETY DATA SHEET

PRODUCT: ARGON

1. PRODUCT INDENTIFICATION AND COMPANY DETAILS

Product: Argon, compressed

Chemical formula: Ar

Company name: Prime Co. (Middle East) Ltd.

Company contact: +971-4-8816820

2. COMPOSITION / INFORMATION ON INGREDIENTS

Substance / Preparation: Substance

Components / Impurities: Contains no other components or impurities which

will influence the classification of product.

CAS Number: 7440-37-1

3. HAZARDS IDENTIFICATION

Hazards identification: Compressed gas in high concentration may cause

dizziness, drowsiness and asphyxiation.

4. FIRST AID MEASURES

Inhalation: Immediately remove to fresh air and call doctor.

Ingestion: This product is gas at normal temperature and pressure. It is not

considered a potential route for exposure.

Eye contact: Flush eyes with water.

5. PHYSICAL & CHEMICAL PROPERTIES

Appearance: Colourless, odourless at normal temperature and

pressure

Odour: None

Physical state: Gas at normal temperature and pressure

Melting point: - 189.35 °C Boiling point: - 185.87 °C

Vapour density: 1.654 kg/m³ at 21.1 °C and 1 atm

Vapour pressure: Not applicable

Solubility in water: 61 mg/l

Flammable limits: Not applicable

Autoignition

Temperature: Not applicable

Molecular weight: 39.95 Molecular formula: Ar



6. FIRE FIGHTING MEASURES

Flammable Properties: Nonflammable.

Suitable extinguishing media: Argon cannot catch fire. Use media appropriate

for surrounding fire.

Products of combustion: None

Specific methods: Heat of fire can build pressure in cylinder, hence move away

from container. Immediately cool cylinder using water.

Special protective equipment for firefighting: Use self contained breathing

apparatus.

7. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions.

In compatible materials: None know. Argon is chemically inert.

8. TOXICOLOGICAL INFORMATION

None known. Argon is a simple asphyxiant.

9. ECOLOGICAL INFORMATION

Ecotoxicity: No known effects

10. DISPOSAL PROCEDURES

Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

11. ACCIDENTAL RELEASE MEASURES

Personal precautions: Argon is a simple asphyxiant. Shut off valve if without risk. Move cylinder to well ventilated area. Evacuate area and ensure adequate ventilation.

Environmental precautions: Keep personnel away. Try to stop release.

12. HANDLING AND STORAGE

Precautions to be taken in handling: Protect cylinders from damage. Do not drag, slide, roll or drop cylinders. Never attempt to lift cylinders by its cap as the cap is intended to protect the valve. Slowly open valve. Close cylinder valve after each use and keep closed even when cylinder is empty. Never apply heat or flame to any part of cylinder.

Precautions to be taken in storage: Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Store cylinders below 50 °C.



13.TRANSPORT INFORMATION

UN Number: 1006 Hazard Class: 2.2

Labeling ADR Label 2: non flammable non toxic gas.

Other information: Avoid transport on vehicles where the load space is not separated from driver's compartment. The vehicle driver must be aware of the potential hazards of the cylinders and knows what to do in the event of an accident or emergency. Before transporting cylinders ensure that they are firmly secured in the vehicle, cylinder valve is closed, valve protection is in place, adequate ventilation and compliance with local regulations.

14. REGULATORY INFORMATION

Labeling of cylinder

- Label 2: non flammable non toxic gas.

15. OTHER INFORMATION

Ensure all national / local regulations are observed and adhered to. Ensure that the operators understand the hazard of nitrogen enrichment. The hazard of asphyxiation is often overlooked and must be stressed during operator training. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

The MSDS is based on reliable sources. Sufficient care has been taken in preparation of this document, however no liability for injury or damage resulting from its use can be accepted.

PRIME CO. (MIIDLE EAST) LTD.

P.O. BOX 17239 JAFZ, DUBAI, U.A.E.

TEL: +971-4-8816820

FAX: +971-4-8815237

Website: www.primeco.ae