according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

000000016095

Version 2.9 Revision Date 12.03.2019 Supersedes 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Solstice® ZE Refrigerant (R-1234ze(E))

SDS-number 00000016095

Type of product Substance

Remarks SDS according to Art. 31 of Regulation (EC) 1907/2006.

Chemical name trans-1,3,3,3-Tetrafluoroprop-1-ene

CAS-No. 29118-24-9

REACH Registration

Number

01-0000019758-54

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Refrigerant

Substance/Mixture

Uses advised against : none

1.3. Details of the supplier of the safety data sheet

Company Honeywell Fluorine Products Honeywell International, Inc.

> Europe B.V. 115 Tabor Road

Stationsplein Zuid-West 961 Morris Plains, NJ 07950-2546

1117 CE Schiphol-Oost USA

Netherlands Telephone +32 16 391 211

Telefax

: PMTEU Product Stewardship: For further information, SafetyDataSheet@Honeywell.com please contact:

1.4. Emergency telephone number

Emergency telephone : +1-703-527-3887 (ChemTrec-Transport)

number +1-303-389-1414 (Medical)

Country based Poison

Control Center

: see chapter 15.1

SECTION 2: Hazards identification

Page 1 / 15

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

00000016095

Version 2.9 Revision Date 12.03.2019 Supersedes 1

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

Gases under pressure Liquefied gas H280 Contains gas under pressure; may explode if heated.

2.2. Label elements

REGULATION (EC) No 1272/2008

Hazard pictograms

 \Diamond

Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may

explode if heated.

Precautionary statements : P260 Do not breathe dust/ fume/ gas/ mist/

vapours/ spray.

P280 Wear protective gloves/ eye protection/

face protection.

P284 In case of inadequate ventilation wear

respiratory protection.

P308 + P313 IF exposed or concerned: Get medical

advice/ attention.

P410 + P403 Protect from sunlight. Store in a well-

ventilated place.

2.3. Other hazards

Warning! Container under pressure.

SECTION 3: Composition/information on ingredients

3.1. Substance

Chemical name	CAS-No. Index-No. REACH Registration Number EC-No.	Classification 1272/2008	Concentration	Remarks
trans-1,3,3,3- Tetrafluoroprop-1-ene	29118-24-9 01-0000019758-54 471-480-0	Press. Gas ; H280	100 %	1*

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

000000016095

Version 2.9

Revision Date 12.03.2019

Supersedes 1

1* - For specific concentration limits see Annexes of 1272/2008

3.2. Mixture

Not applicable

Occupational Exposure Limit(s), if available, are listed in Section 8. For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice:

First aider needs to protect himself. Move out of dangerous area. Keep warm and in a quiet place. Show this safety data sheet to the doctor in attendance. Take off all contaminated clothing immediately.

Inhalation:

If inhaled, remove to fresh air. Get medical attention if irritation develops and persists.

Skin contact:

Rapid evaporation of the liquid may cause frostbite. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. Call a physician if irritation develops or persists.

Eye contact:

Immediately flush eye(s) with plenty of water. Call a physician immediately.

Ingestion:

Ingestion is unlikely because of the physical properties and is not expected to be hazardous. As this product is a gas, refer to the inhalation section.

4.2. Most important symptoms and effects, both acute and delayed

no data available

4.3. Indication of any immediate medical attention and special treatment needed

no data available

See Section 11 for more detailed information on health effects and symptoms.

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

000000016095

Version 2.9

Revision Date 12.03.2019

Supersedes 1

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water mist

Dry powder

Foam

Carbon dioxide (CO2)

5.2. Special hazards arising from the substance or mixture

Contents under pressure.

Heating will cause pressure rise with risk of bursting

Cool closed containers exposed to fire with water spray.

Product is not combustible under normal conditions.

However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.

Do not allow run-off from fire fighting to enter drains or water courses.

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Some risk may be expected of corrosive and toxic decomposition products.

Fire may cause evolution of:

Hydrogen fluoride

Carbon oxides

Carbonyl halides

Halogenated compounds

5.3. Advice for firefighters

Wear full protective clothing and self-contained breathing apparatus.

Exposure to decomposition products may be a hazard to health.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. In the event of fire, cool tanks with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Avoid skin contact with leaking liquid (danger of frostbite). Use personal protective equipment. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

000000016095

Version 2.9

Revision Date 12.03.2019

Supersedes 1

Prevent further leakage or spillage if safe to do so. The product evapourates readily. Prevent spreading over a wide area (e.g. by containment or oil barriers).

6.3. Methods and materials for containment and cleaning up

Do not direct water spray at the point of leakage. Allow to evaporate.

6.4. Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Exhaust ventilation at the object is necessary.

Advice on protection against fire and explosion:

Do not spray on a naked flame or any incandescent material. Keep away from direct sunlight. Fire or intense heat may cause violent rupture of packages. Vapours may form explosive mixtures with air. The product is not easily combustible.

Hygiene measures:

Avoid breathing vapours, mist or gas. Keep working clothes separately.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions:

Keep containers tightly closed in a cool, well-ventilated place. Keep only in the original container at temperature not exceeding 50°C Keep away from direct sunlight.

Advice on common storage:

Do not store together with: Oxidizing agents

7.3. Specific end use(s)

no additional data available

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

00000016095

Version 2.9 Revision Date 12.03.2019

Supersedes 1

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits:

Components	Basis / Value type	Value / Form of exposure	Exceeding Factor	Remarks
trans-1,3,3,3-Tetrafluoroprop-1-ene	HONEYWELL TWA	800 ppm		We are not aware of any national exposure limit.

TWA - Time weighted average

DNEL/ PNEC-Values

Component	End- use/impact	Exposure duration	Value	Exposure routes	Remarks
trans-1,3,3,3- Tetrafluoroprop-1-ene	Workers / Long-term systemic effects		3902 mg/m3	Inhalation	
trans-1,3,3,3- Tetrafluoroprop-1-ene	Consumers / Long-term systemic effects		830 mg/m3	Inhalation	

Component	Environmental compartment / Value	Remarks
trans-1,3,3,3-Tetrafluoroprop-1-ene	Fresh water: 0,1 mg/l	Assessment factor: 1000

8.2. Exposure controls

Occupational exposure controls

The Personal Protective Equipment must be in accordance with EN standards:respirator EN 136, 140, 149; safety glasses EN 166; protective suit: EN 340, 463, 468, 943-1, 943-2; gloves EN 374, 511; safety shoes EN-ISO 20345.

The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Avoid inhalation of vapour or mist.

Engineering measures

Local exhaust

Personal protective equipment

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

00000016095

Version 2.9 Revision Date 12.03.2019 Supersedes 1

Respiratory protection:

In case of insufficient ventilation wear suitable respiratory equipment.

Self-contained breathing apparatus (EN 133)

Hand protection:

Protective gloves against cold

(EN 511)

Gloves must be inspected prior to use.

Replace when worn.

Eye protection:

Goggles

Skin and body protection:

Wear suitable protective equipment.

Protective footwear

Environmental exposure controls

Handle in accordance with local environmental regulations and good industrial practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form : Liquefied gas

Colour : colourless

Odour : slight

ether-like

Boiling point/boiling range : -19 °C

Flash point : Not applicable

Auto-ignition temperature : 368 °C

Lower explosion limit : No LEL and UEL was assigned at standard testing conditions,

20°C.

Exhibits flame limits at temperatures in excess of 28° C.

Upper explosion limit : No LEL and UEL was assigned at standard testing conditions,

20°C.

Exhibits flame limits at temperatures in excess of 28° C.

Vapour pressure : 4.271 hPa

at 20 °C

Page 7 / 15

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

000000016095

Version 2.9 Revision Date 12.03.2019

Supersedes 1

Vapour pressure : 11.152 hPa

at 54,4 °C

Density : 1,17 g/cm3

at 21,1 °C

pH : neutral

Water solubility : 0,373 g/l

Partition coefficient: n-

octanol/water

: log Pow 1,6

Relative vapour density : 4

(Air = 1.0)

9.2 Other Information

no additional data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Hazardous decomposition products formed under fire conditions.

To avoid thermal decomposition, do not overheat.

10.3. Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4. Conditions to avoid

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Can form a combustible mixture with air at pressures above atmospheric pressure.

10.5. Incompatible materials

Reactions with alkali metals.

10.6. Hazardous decomposition products

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

00000016095

Version 2.9

Revision Date 12.03.2019

Supersedes 1

Halogenated compounds Carbon oxides Hydrogen fluoride Carbonyl halides

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity: Not applicable study technically not feasible

Acute dermal toxicity: no data available study technically not feasible

Acute inhalation toxicity:

LC0

Species: Rat

Value: > 207000 ppm Exposure time: 4 h

Method: OECD Test Guideline 403

Skin irritation: Species: Rabbit

Result: No skin irritation

Method: OECD Test Guideline 404

Eye irritation: no data available study technically not feasible

Respiratory or skin sensitisation:

Species: human

Result: Does not cause skin sensitisation.

Repeated dose toxicity:

Species: Rat

Application Route: Inhalation

Exposure time: 90 d NOEL: 5000 ppm

Method: OECD Test Guideline 413

Note: Subchronic toxicity

Carcinogenicity:
Note: no data available

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

00000016095

Version 2.9 Revision Date 12.03.2019

Supersedes 1

Germ cell mutagenicity:

Test Method: Chromosome aberration test in vitro

Cell type: Human lymphocytes

Result: negative

Method: OECD Test Guideline 473

Test Method: Ames test

Result: negative

Test Method: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)

Species: Mouse

Cell type: Micronucleus Application Route: Inhalation Method: OECD Test Guideline 474

Result: negative

Reproductive toxicity:

Test Type: Two-generation study Method: OECD Test Guideline 416

Species: Rat

Route of Application: Inhalation

General Toxicity - Parent: NOEL: > 20.000 ppm General Toxicity F1: NOEL: > 20.000 ppm

Method: OECD Test Guideline 414

Species: Rat

Route of Application: Inhalation

General Toxicity Maternal: NOEC: 15.000 ppm Developmental Toxicity: NOAEC: 15.000 ppm

Aspiration hazard: no data available

Other information:

Cardiac Sensitization (dog): No effects

SECTION 12: Ecological information

12.1. Toxicity

Toxicity to fish:

LC0 static test

Species: Cyprinus carpio (Carp)

Value: > 117 mg/l Exposure time: 96 h

Method: OECD Test Guideline 203

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

00000016095

Version 2.9 Revision Date 12.03.2019

Supersedes 1

Toxicity to aquatic plants:

NOEC Growth rate Species: Algae Value: > 170 mg/l Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC Biomass Species: Algae

Value: > 170 mg/l Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to aquatic invertebrates:

EC50 static test

Species: Daphnia magna (Water flea)

Value: > 160 mg/l Exposure time: 48 h

Method: OECD Test Guideline 202

12.2. Persistence and degradability

Biodegradability:

aerobic

Result: Not readily biodegradable.

12.3. Bioaccumulative potential

No bioaccumulation is to be expected (log Pow <= 4).

12.4. Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment

no data available

12.6. Other adverse effects

no data available

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

00000016095

Version 2.9 Revision Date 12.03.2019 Supersedes 1

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product:

Dispose according to legal requirements. Contact manufacturer.

Packaging:

Legal requirements are to be considered in regard of reuse or disposal of used packaging materials

Further information:

Provisions relating to waste:

EC Directive 2006/12/EC; 2008/98/EEC

Regulation No. 1013/2006

For personal protection see section 8.

SECTION 14: Transport information

ADR/RID

UN Number : 3163

Description of the goods : LIQUEFIED GAS, N.O.S.

(TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE)

Class : 2 Classification Code : 2A Hazard Identification : 20

Number

ADR/RID-Labels : 2.2 Environmentally hazardous : no

IATA

UN Number : 3163

Description of the goods : Liquefied gas, n.o.s.

(trans-1,3,3,3-Tetrafluoroprop-1-ene)

Class : 2.2 Hazard Labels : 2.2

IMDG

UN Number : 3163

Description of the goods : LIQUEFIED GAS, N.O.S.

(TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE)

Class : 2.2
Hazard Labels : 2.2
EmS Number : F-C, S-V
Marine pollutant : no

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

00000016095

Version 2.9 Revision Date 12.03.2019

Supersedes 1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison Control Center

Country	Phone Number
Austria	+4314064343
Belgium	070 245245
Bulgaria	(+)35929154233
Croatia	(+3851)23-48-342
Cyprus	no data available
Czech Republic	+420224919293; +420224915402
Denmark	82121212
Estonia	16662; (+372)6269390
Finland	9471977
France	+33(0)145425959
Greece	no data available
Hungary	(+36-80)201-199
Iceland	5432222
Ireland	+353(1)8092166
Italy	+39 0649906140
	Berlin : 030/19240
	Bonn : 0228/19240
	Erfurt : 0361/730730
Germany	Freiburg : 0761/19240
	Göttingen : 0551/19240
	Homburg : 06841/19240
	Mainz : 06131/19240
	Munich : 089/19240
Latvia	+37167042473

Country	Phone Number
Liechtenstein	no data available
Lithuania	+370532362052
Luxembourg	070245245; (+352)80002-5500
Malta	no data available
Netherlands	030-2748888
Norway	22591300
Poland	no data available
Portugal	808250143
Romania	no data available
Slovakia (NTIC)	+421 2 54 774 166
Slovenia	no data available
Spain	+34915620420
Sweden	112 (begär Giftinformation);+46104566786
Switzerland	145
United Kingdom	no data available

Other inventory information

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

000000016095

Version 2.9 Revision Date 12.03.2019

Supersedes 1

US. Toxic Substances Control Act On TSCA Inventory

Australia. Industrial Chemical (Notification and Assessment) Act On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI)
On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act Not in compliance with the inventory

China. Inventory of Existing Chemical Substances On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

A chemical safety assessment has been carried out. In accordance to the article 14(4) of the REACH regulation (EC) No. 1907/2006, exposure estimation and risk characterization is not required.

SECTION 16: Other information

Text of H-statements referred to under heading 3

trans-1,3,3,3-Tetrafluoroprop-1- : H280 Contains gas under pressure; may explode if heated.

Further information

All directives and regulations refer to amended versions.

Vertical lines in the left hand margin indicate a relevant amendment from the previous version.

Abbreviations:

EC European Community
CAS Chemical Abstracts Service

DNEL Derived no effect level

PNEC Predicted no effect level

D.D. Variational and Land Linear In-

vPvB Very persistent and very biaccumulative substance

Page 14 / 15

according to Regulation (EC) No. 1907/2006



Solstice® ZE Refrigerant (R-1234ze(E))

00000016095

Version 2.9

Revision Date 12.03.2019

Supersedes 1

PBT Persistent, bioaccmulative und toxic substance

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.

This information should not constitute a guarantee for any specific product properties.